


Product Technical Data

Cat. NO : 5100 - 5200

Name : STANDARD GAS TORCH

Created by : 16/04/2026

Product:	Gas torch	Application fields: Plumbing, odd-job, heating, deburring, de-icing
Activities:	Plumbing / Odd-job	
User:	General public	
Energy:	Butane	

Cat. N° 5100	Cat. N° 5200
	
Description cat. N° 5100 Butane gas torch Rubber hose, 1.50 m long, ISO 3821 Butane cylinder connection: depending on country 1 sharp tip flame: length 70 mm	Description cat. N° 5200 Butane gas torch Rubber hose, 1.50 m long, ISO 3821 Butane cylinder connection: depending on country 1 sharp tip flame: length 70mm 1 Cercoflam: enveloping flame 1 paint burner: flat flame

Technical features		
Butane gas flow (g/h) at 1.5 bar	310 g/h	
Power	4,3 kW	14700 BTU
Flame Temperature	1850 °C	3300 °F
Soldering capacity on copper tube	Sharp tip flame	Cercoflam
Max. diameter of copper tube with CuPh solder	Ø 18 mm	Ø 24 mm

Spare Parts	
Paint Burner	Cat. N° 4716
Cercoflam	Cat. N° 7693



Packaging	Weight (g)	Width (mm)	Depth (mm)	Height (mm)
Cardboard box, 4x5100	2435	430	327	105
Cardboard box, 4x5200	2860	430	327	105

IMPORTANT : Read instructions before use.

GUILBERT EXPRESS reserves the right to change product characteristics without previous notice. Actual products may differ from photographs.

<https://www.express.fr/en/>

GUILBERT EXPRESS

10 rue Henry Delbast - 77183 Croissy-Beaubourg - Tél: 0.825.800.251 - Fax: 0.825.800.238