

Product Technical Data Sheet

CAT. NO. 848

Description : Moisture absorption

Issued on: 17/12/2025

Product:	Drying powder (moisture-absorbing granules)
Applications:	Bitumen roofing Plumbing Sheet metal roofing
Users:	Professional
Energy:	Physico-chemical

Packaging
1 kg container

Description

	Absorption *	Retention (*)
In a solution containing 0.2% NaCl	approx. 90 g/g	approx. 60 g/g
In a solution containing 0.9% NaCl	approx. 52 g/g	approx. 35 g/g

*Values provided for guidance only – may vary depending on several parameters (particle size, type of liquid absorbed, etc.)

INSTRUCTIONS AND RECOMMENDATIONS FOR USE

Spread the moisture absorber over the surface to be dried.
Wait a few minutes. The granules will swell and form a gel.
Following use, collect the gel using a brush and shovel.

The gel will become liquid again when acidified (pH<1) or when sodium chloride (NaCl) is added.
Next, filter the solution to recover the granules.
The gel and the granules can be air-dried or placed in an oven to remove the water (temperature below 50°C to avoid molecular degradation).

Due to its properties, the product must be protected from humidity.
It should be stored in a dry, ventilated environment at a temperature below 50°C.
Ensure that the packaging is properly closed following use.

Non-hazardous to health: the product may be disposed of as solid waste or incinerated in an appropriate facility.

Non-biodegradable: avoid releasing large quantities into the environment or the sewage system (risk of clogging and soil salinization).



Note: The content of this technical data sheet is based on our knowledge and experience of the product. This content is provided for information only and we cannot be held liable for it in each individual case.

IMPORTANT: Read the instruction manual before use

GUILBERT EXPRESS reserves the right to change product characteristics without prior notice. Actual products may differ from photographs.

<https://www.express.fr/>

GUILBERT EXPRESS

10 rue Henry Delbast - 77183 Croissy-Beaubourg - Tél: 0.825.800.251 - Fax: 0.825.800.238