

GUILBERT EXPRESS

10 rue Henry Delbast
77183 Croissy-Beaubourg
Tél: 0.825.800.251 - Fax: 0.825.800.238

Product datasheet

Cat. No. 460	
Created on	08/06/2020
Modified on	06/05/2024
Issue	C

Name	Vulcane One
Cat. N°	G460

Description

Piezo ignition
Flow rate controlled by regulator
Can be pointed downward instantly
Hanging ring
Accurate gas flow control
Removable stabilizer stand
Attractive plastic casing
Handle with safety cut-off
MAPP and propane gas compatible
Continuous or trigger-controlled flame

Areas of application

Plumbing, welding, brazing, flame cleaning, unjamming, burning, defrosting.


Technical data

Gas	Pressure		Consumption	Power		For tube	"Turbo" type flame		
	bar	psi		g/h	kW		BTU/h	Cu Ø (mm)	Ø (mm)
XPRESS 2400	1.4	20	204	2.7	9200	10 - 22	18	80	
Propane	1.4	20	227	3.1	10690	10 - 22	18	80	

Spare parts

Designation	Cat. No.
100% propylene cylinder	2400
Stabiliser stand	4702
Extension hose	4770

Vulcane ONE weight: 375 g
Weight in packaging on hang tab: 450 g


2400

4770

4702

IMPORTANT: Read instructions before use

GUILBERT EXPRESS reserves the right to change products without prior notice. Actual products may differ from photographs